

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
2 March 2006 (02.03.2006)

PCT

(10) International Publication Number
WO 2006/022125 A1(51) International Patent Classification⁷: **B60L 11/18, B60K 6/04**(74) Agent: **ITEC INTERNATIONAL PATENT FIRM;**
Uchisaiwaicho Dai Bldg., 3-3, Uchisaiwai-cho, 1-chome,
Chiyoda-ku, Tokyo 1000011 (JP).(21) International Application Number:
PCT/JP2005/014148

(22) International Filing Date: 27 July 2005 (27.07.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-244763 25 August 2004 (25.08.2004) JP
2005-074874 16 March 2005 (16.03.2005) JP(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP];** 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **HOSHIBA, Takeshi [JP/JP];** c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **AMANO, Masaya [JP/JP];** c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: **ELECTRIC VEHICLE AND CONTROL METHOD OF THE SAME**

(57) Abstract: In response to a decrease in observed battery voltage V_b to or below a preset threshold value V_{s1} , the control procedure of the invention closes the gates of an inverter for an air conditioner to stop a supply of electric power to the air conditioner (at a time point t_1). In response to a further decrease in observed battery voltage V_b to or below a preset threshold value V_{m1} , the control procedure closes the gates of inverters for motors $MG1$ and $MG2$ to stop supplies of electric power to the motors $MG1$ and $MG2$ (at a time point t_2). The threshold values V_{s1} and V_{m1} are set to keep the battery voltage V_b at or above a minimum required voltage for proper operations of an electric power steering (EPS). This arrangement guarantees the minimum required voltage for proper operations of the EPS and accordingly ensures the stable steering performance even in the event of a voltage decrease of the battery.

WO 2006/022125 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.